

Solar systems from Schweizer

Schweizer

Tender specifications PV mounting system

Green roof MSP-FR-G

- **Technical description:**

Aerodynamically designed flat roof mounting system for photovoltaic modules on flat roofs, including all system components. Planning and necessary structural design with verification using the manufacturer's own design software. Suitable for green roofs.

- **System properties:**

Nominal elevation of 10°. Installation is carried out without penetrating the roof; the load is transferred via ballasting. Roof pitch $\leq 3.0^\circ$ (optionally with on-site connection to the roof substructure up to 10°).

Maximum block size 15 m x 15 m (thermal separation). The minimum distance from the roof edge is ≥ 0.15 m. Roof unevenness of up to 2° can be accommodated. Pre-manufactured components, no drilling or cutting. Pressure load on the roof can be minimised by selecting base plate lengths. Universal clamps for solar module frames

with 28–50 mm frame height. Potential equalisation and tested lightning current carrying capacity.

- **Tests and certificates:**

The system is certified according to TÜV 2 PFG 1794, including monitoring by TÜV

The clamps and cross connectors are certified by DiBt, approval number 14.4-926

The continuity of the earthing and corrosion resistance have been tested by VDE renewables Report ET2_184427

The lightning current carrying capacity and corrosion resistance have been tested by the

DEHN-Test centre

Report 1863

- **Material:**

- Construction Aluminium, support system made of ZM-coated steel.
- Small parts made of stainless steel and protective coating without plasticiser migration.